



Ø.080 [2.03] REF

R.007±.001 [0.19±0.03]

## NOTES:

- N <del>-</del>
- HERMETICITY 1E(-8) STD CC/SEC @1ATM.
  FINISH (PLATING THICKNESS IN MICRO-INCHES)
  GLASS + KOVAR
  GOLD PL.50 MIN. OVER NICKEL PL.100 MIN.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.



TITLE an INFINIT® brand

⊳	SIZE			<			UNL	
3F	CAGE CODE	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY	X = ±.2 [5.08] XX = ±.02 [.51] XX = ±.005[.13]			TOLERANCES	ı	ESS OTHER
3FKR5	DE		X=±.2 [5.08] FRACTIONS XX=±.02 [.51] ±1/32 XXX=±.005[.13] ANGLES±1°		NCES:	DIMENSIONS	WISE SPECIF	
K.DANG	DRAWN BY		120 [3048] < L ≤ 300 300 [762	12 [305] < L < 60 [1524] = +2 [51] /-0 60 [1524] < L < 120 [3048] = +4 [102] /-0	L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0		DIMENSIONS IN [] ARE MILLIMETERS	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES
FM1015-3	ITEM NO.	NCE ONLY.	120 [3048] < L \( \le 300 [7620] = +6 [152] / -0 \\ 300 [7620] < L = +5%L / -0 \\ \]	L ≤ 12 [305] = +1 [25] / -0	CABLE LENGTH (L) TOLERANCES:	"	ONS ARE INCHES	
		SCALE N	THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRVIEW MICROPHORATION ALL RIGHT'S RESERVED.  SHEET 1 OF 1					
Φ	REV	N/A	1	CORPORATION. SERVED.	OCUMENT	ON AND	<u> </u>	THIRD-ANGLE PROJECTION