

NAME		
DESCRIPTION	8 PIN RECTANGULAR MALE	
TYPE		

0 0.00

.200 5.08

.540 [13.72]

PIN 2,4,6	NAME TEMP	DESCRIPTION TYPE Analog Temperature Sensor Output Power Ground Power		 LEVEL
2,4,6	GND	Ground	Power	
3	Tx/Rx	TTL Hi = Transmit Mode, TTL Lo or No Connection = Receive Mode	Input	5V TTL
5,7	+VDC	Min: +12V / Max: 30V	Power	
œ	SGND	Signal Ground	Input	

DETAIL A


Fairview Microwave FM15B5003 S/N: XXXXXXX D/C: YYWW

LABEL

STANDARD TOLERANCES
.X ±0.2
.XX ±0.01
.XXX ±0.005

*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES

 $\underline{\rm NOIE}$: SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE. TYPICAL PERFORMANCEAT VDC AT 25 °C IN A 50 Ω SYSTEM.



Fairview Microwave

an INFINIT® brand

III III III

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm]. CAD FILE DWG NO FM15B5003 SHEET 1 OF 1 SCALE N/A CAGE CODE SIZE \triangleright 3FKR5