

## NOTES:

- LABEL PER ILS-100-03 (FOR INTERNAL USE ONLY). LABEL
- 2 LOCATION SHOWN IS FOR REFERENCE ONLY.
  WALL THICKNESS FOR MOUNTING MUST BE .98 [25.0] MINIMUM.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.



an INFINIT® brand

HITE

A |  $X = \pm .2$  [5.08]  $XX = \pm .02$  [.51]  $XXX = \pm .005$  [.13] UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS CAGE CODE 3FKR5 ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY. FRACTIONS ± 1/32 ANGLES ± 1° AKRESOWSK L ≤ 12 [305] = +1 [25] / 0
12 [305] < L ≤ 60 [4524] = +2 [51] / 0
60 [1524] < L ≤ 120 [3048] = +4 [102] / 0
120 [3048] < L ≤ 300 [7620] = +6 [182] / 0
300 [7620] < L = +5%L / 0 CABLE LENGTH (L) TOLERANCES: ITEM NO. FM51243 N/A REV