

NOTES:

- CABLES 84" AND UNDER HAVE 1 LABEL CENTERED. CABLES OVER 84" HAVE 2 LABELS, ONE AT EACH END 12.0" FROM THE END OF THE CONNECTOR. 6" FROM CABLE END 1 PLACE FOR ALL LENGTHS OF CABLE.

Ņ

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES



TITLE

SIZE		3000	× × × × × × ×		S.
CAGE CODE	ALL DIME	X=±2 [5.08] FRACTIONS XX=±02 [.51] ±1/32 XXX=±.005[.13] ANGLES±1°		TOLERANCES:	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS
	NSIONS SHO			CES:	
DRAWN BY	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY	L ≤ 12 [305] = +1 [25] / 0 12 [305] < L ≤ 60 [1624] = +2 [51] / 0 60 (1624] < L ≤ 120 [3048] < +4 [102] / 0 120 [3048] < L ≤ 300 [7620] = +6 [152] / 0 300 [7620] < L = +5%L / 0		CABLE LENGTH	WISE SPECIFIED LEADING DIMENSIO
ITEM NO.	ENCE ONLY.			CABLE LENGTH (L) TOLERANCES:	IONS ARE INCHES
REV	SCALE N/A	SHEET OF 1	DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRVIEW MICROWAVE CORPORATION. ALL RIGHTS RESERVED.	THE INFORMATION AND	THIRD-ANGLE PROJECTION

⊳

3FKR5

K.DANG

FMCA2566