

WR-42 Standard Gain Horn with 15 dBi gain, End Launch
2.92mm Female connector, with Pre-Installed L Mount



FM2WAN042-15ELKF

Features

- 18 GHz to 26.5 GHz
- WR-42 Waveguide Band
- 15 dBi Nominal Gain
- 2.92mm Female End Launch Connector
- Pre-Installed L Mount
- Integrates with Positioning Systems

Applications

- Antenna Measurements
- Wireless Communication
- Laboratory Use
- Microwave Radio Systems
- Radome Testing
- Automotive Antenna Test Solutions
- Radar Cross Section
- Satellite Antenna Testing

Description

The FM2WAN042-15ELKF standard gain horn antenna with pre-installed L mount (also known as waveguide horn) from Fairview Microwave is part of our comprehensive selection of waveguide antennas. This standard gain horn is mated with a WR-42 to 2.92mm female end launch waveguide to coaxial adapter and operates from 18 GHz to 26.5 GHz.

Our FM2WAN042-15ELKF standard gain horn antenna with pre-installed L mount has a nominal gain of 15 dBi with a Horizontal and Vertical HPBW (Half Power Beam Width) of 31 dB and 32 dB respectively. Fairview Microwave's 2.92mm female end launch to WR-42 standard gain horns are available in 10, 15 and 20 dBi models with pyramidal shape and connectorized input.

Waveguide antennas, such as the FM2WAN042-15ELKF are used in a wide variety of applications due to the high-power handling capability, low loss, high directivity, and near constant electrical performance. Our WR-42 waveguide antennas with 2.92mm female end launch interface is part of over 40,000 RF, microwave and millimeter wave components from Fairview Microwave available worldwide and ship same day.

Configuration

Design	WR-42
Coaxial Interface	2.92mm Female

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	18		26.5	GHz
Gain		15		
Horizontal Half Power Beam Width		31		Degrees
Vertical Half Power Beam Width		32		
Waveguide to Coaxial Adapter				
VSWR			1.3:1	

Mechanical Specifications

Size	
Length	7.372 in [187.25 mm]
Width	5.978 in [151.84 mm]
Height	4.092 in [103.94 mm]
Weight	0.7595 lbs [344.5 g]

WR-42 Standard Gain Horn with 15 dBi gain, End Launch
2.92mm Female connector, with Pre-Installed L Mount



FM2WAN042-15ELKF

RF Connector

Type 2.92mm Female
Specification End Launch

Waveguide Interface


Waveguide Size WR-42

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:



Typical Performance Data




WR-42 Standard Gain Horn with 15 dBi gain, End Launch
2.92mm Female connector, with Pre-Installed L Mount




FM2WAN042-15ELKF



WR-42 Standard Gain Horn with 15 dBi gain, End Launch 2.92mm Female connector, with Pre-Installed L Mount



FM2WAN042-15ELKF



WR-42 Standard Gain Horn with 15 dBi gain, End Launch 2.92mm Female connector, with Pre-Installed L Mount from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.


For additional information on this product, please click the following link: [WR-42 Standard Gain Horn with 15 dBi gain, End Launch 2.92mm Female connector, with Pre-Installed L Mount FM2WAN042-15ELKF](#)

URL: <https://www.fairviewmicrowave.com/wr-42-standard-gain-horn-15-dbi-2.92mm-fm2wan042-15elkf-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

FM2WAN042-15ELKF CAD Drawing

WR-42 Standard Gain Horn with 15 dBi gain, End Launch 2.92mm Female connector, with Pre-Installed L Mount



REVISION		DATE	CHANGED BY	APPROVED
ZONE	REV	DESCRIPTION	INITIAL RELEASE	
A	A			KHIE/TPAS

Fairview Microwave
an INFINITI® brand

Website: www.FairviewMicrowave.com
Phone: 1.800.715.4396 | 1.972.649.6678

SCALE: NONE
SHEET: 1 OF 1

INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5

DESCRIPTION: WR-42 STANDARD GAIN HORN WITH 15 dBI GAIN, END LAUNCH 2.92mm FEMALE CONNECTOR WITH PRE-INSTALLED L MOUNT

SIZE: A
CAGE CODE: 3FKR5
DRAWN BY: HBAKKE
ITEM NO.: FM2WAN042-15ELKF
REV: A

UNLESS OTHERWISE SPECIFIED, LEADING DIMENSIONS ARE IN INCHES. DIMENSIONS IN [] ARE MILLIMETERS.

TOLERANCES:
 .X = ±.2 [5]
 .XX = ±.02 [0.5]
 .XXX = ±.005 [0.13]

FRACTIONS: ± 1/32
 ANGLES: ± 1°

CABLE LENGTH TOLERANCES:
 ≤ 12 [305] ± .60 [15.24] = +.2 [5] / -0
 > 12 [305] ≤ 60 [1524] = +.4 [10.2] / -0
 > 60 [1524] ≤ 120 [3048] = +.4 [10.2] / -0
 > 120 [3048] ≤ 300 [7620] = +.6 [15.2] / -0
 > 300 [7620] = +.6 [15.2] / -0

ALL DIMENSIONS ARE FOR REFERENCE ONLY. UNDIMENSIONED NON-CRITICAL FEATURES MAY VARY IN SIZE AND LOCATION. COLORS MAY VARY.

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE ARE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVISION CONTRARY TO U.S. LAWS PROHIBITED.

FM DS Rev-D4 Alt2b