

### 3.5mm Male to Male Thru Calibration Kit Component for Precision Up to 34 GHz

3.5mm male to male thru calibration kit component, part number FMAD1130, from Fairview Microwave is in-stock and ships same day. This 3.5mm precision thru circuit can be used for calibration of most vector network analyzers (VNA), cable analyzers or site analyzers. Impedance and VSWR specifications for this 3.5mm thru calibrating component are provided in the datasheet. Precision control of the impedance and electrical length allow for OSLT analyzer calibrations over the complete frequency range of the connector interface provided.

Fairview's 3.5mm thru circuit calibration component FMAD1130 datasheet specifications and outline drawing are shown in this PDF below. Our extensive offering for RF, microwave and millimeter wave components allows designers to configure and customize their test solutions however they like. From calibration kit replacement to SOLT / OSLT VNA calibration, Fairview Microwave has the right calibration kit components to meet your needs and ship them same-day.



#### Features:

- Controlled Impedance
- Replaces Damaged Calibrating Kit Components
- Controlled Electrical Length
- Precision Interfaces
- In Stock and Ready to Ship

#### Applications:

- SOLT or OSLT Calibration
- VNA Calibration
- Device Characterization
- De-embedding
- Replacement Calibration Kits

#### Electrical Specifications

Description	Min	Typ	Max	Units
Frequency Range	DC		34	GHz
Impedance		50		Ohms
VSWR			1.08:1	
Electrical Delay		59		ps

#### Performance by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC-18	18-26.5				GHz
VSWR, Max	1.05:1	1.08:1				

Electrical Specification Notes:  
 Values at 25° sea level.

#### Mechanical Specifications

<b>Size</b>	
Length	0.88 in [22.35 mm]
Width/Diameter	0.5 in [12.7 mm]
Pin Depth	0 to 0.003 in
<b>Connector 1</b>	
Connector Type	3.5mm Male
Body Material and Plating	Beryllium Copper, Gold
<b>Connector 2</b>	
Connector Type	3.5mm Male
Connector Body Material and Plating	Beryllium Copper, Gold

#### Environmental Specifications

Fairview Microwave  
 301 Leora Ln., Suite 100  
 Lewisville, TX 75056  
 Tel: 1-800-715-4396 / (972) 649-6678  
 Fax: (972) 649-6689  
[www.fairviewmicrowave.com](http://www.fairviewmicrowave.com)  
[sales@fairviewmicrowave.com](mailto:sales@fairviewmicrowave.com)

**Compliance Certifications** (see [product page](#) for current document)

**Plotted and Other Data**

Notes:


- Values at +25 °C, sea level

3.5mm Male to Male Thru Calibration Kit Component for Precision Up to 34 GHz from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [3.5mm Male to Male Thru Calibration Kit Component for Precision Up to 34 GHz FMAD1130](#)

URL: <https://www.fairviewmicrowave.com/3.5mm-male-calibration-kit-component-thru-34-ghz-fmad1130-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.



STANDARD TOLERANCES	
.X	±0.2
.XX	±0.01
.XXX	±0.005

\*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES

<b>FAIRVIEW MICROWAVE INC.</b> ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM		NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].				
		DWG NO <b>FMAD1130</b>		CAGE CODE <b>3FKR5</b>		
TITLE <b>3.5mm Male to Male Thru Calibration Kit Component for Precision Up to 34 GHz</b>		CAD FILE 01/17/18	SHEET	SCALE N/A	SIZE A	CN2245