

## RF Adapter, SMPS Male (Plug) Full Detent to 1.85mm Male (Plug) Adapter

Full detent SMPS male to 1.85mm male adapter part number FMAD9992 from Fairview Microwave is in-stock and ships same day. This Fairview SMPS to 1.85mm adapter has a male to male gender configuration and is built of durable stainless steel. FMAD9992 SMPS male to 1.85mm male adapter operates to 67 GHz.

RF adapters can be used to enable connections between two connector types that would otherwise not mate. Certain RF adapter configurations can also be used to protect connectors on expensive equipment where the number of connect and disconnect cycles is high. An RF, microwave, or millimeter wave adapter is connected to the equipment and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Fairview Microwave also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

### Electrical Specifications

Description	Min	Typ	Max	Units
Frequency Range	DC		67	GHz
Insertion Loss			0.7	dB

### Mechanical Specifications

<b>Size</b>	
Length	0.66 in [16.79 mm]
Width	0.35 in [8.99 mm]
Height	0.35 in [8.99 mm]
Weight	0.01 lbs [3.18 g]

Description	Connector 1	Connector 2
Type	SMPS Male	1.85mm Male
Connection Method	Full Detent	
Polarity	Standard	Standard
Mating Cycles, Min	500	500

### Material Specifications

Description	Connector 1	Connector 2
Type	SMPS Male	1.85mm Male
Contact Material	Beryllium Copper	Beryllium Copper
Contact Plating	Gold	Gold
Contact Plating Spec.	50 µin minimum	50 µin minimum
Insulation Material	PEI	PEI
Outer Contact Material	Passivated Stainless Steel	Passivated Stainless Steel
Body Material	Passivated Stainless Steel	Passivated Stainless Steel

### Environmental Specifications

<b>Temperature</b>	
Operating Range	-55 to -165 deg C



### Configuration:

- Full Detent SMPS Male Connector 1
- 1.85mm Male Connector 2
- 50 Ohm
- Straight Body Geometry

### Features:

- 50 µin minimum contact plating
- Gold Plated Beryllium Copper Contact

### Applications:

- Enables Between Series Connections
- General Purpose Test

Fairview Microwave  
 301 Leora Ln., Suite 100  
 Lewisville, TX 75056  
 Tel: 1-800-715-4396 / (972) 649-6678  
 Fax: (972) 649-6689  
[www.fairviewmicrowave.com](http://www.fairviewmicrowave.com)  
[sales@fairviewmicrowave.com](mailto:sales@fairviewmicrowave.com)

Humidity	MIL-STD-202, Method 106, Less Step 7B
Shock	MIL-STD-202, Method 213, Condition I
Vibration	MIL-STD-202, Method 204, Condition D
Thermal Shock	MIL-STD-202, Method 107, Condition B

**Compliance Certifications** (see [product page](#) for current document)

**Plotted and Other Data**

Notes:

RF Adapter, SMPS Male (Plug) Full Detent to 1.85mm Male (Plug) Adapter from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [RF Adapter, SMPS Male \(Plug\) Full Detent to 1.85mm Male \(Plug\) Adapter FMAD9992](#)

URL: <https://www.fairviewmicrowave.com/full-detent-smps-male-to-1.85mm-male-adapter-mil-std-202-method-106-less-step-7b-with-passivated-stainless-steel-body-fmad9992-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

