

FMC0438315-XX DATA SHEET

RA SMA Male to BNC Female Bulkhead Cable RG-316 Coax

Electrical Specifications

Frequency Range DC to 3 GHz Impedance 50 Ohms Velocity of Propagation 70 %

Mechanical Specifications

Temperature

Temperature Operating Range -65 to +165 deg C

Size

Diameter 0.689 in [17.5 mm]

Cable Color Black

Cable

ver
mm]

Connectors

Description	Connector 1	Connector 2		
Туре	SMA Male Right Angle	BNC Female Bulkhead		
Configuration	Right Angle	Straight		
Mount Method		Bulkhead		
Inner Conductor Material & Platin	ng Brass, Gold	Brass, Gold		
Inner Conductor Plating Spec.	50µ in. minimum	30µ in. minimum		
Hex Size	5/16 inch			
Body Material & Plating	Brass, Nickel	Brass, Nickel		
Body Plating Spec.	100µ in. minimum	100µ in. minimum		
Dielectric Type	Teflon	PTFE		

Compliance Certifications (visit www.FairviewMicrowave.com for current document)

Notes:

- Values at +25 °C, sea level
- BNC Female to RA SMA Male Cables



Configuration:

- SMA Male Right Angle
- BNC Female Bulkhead
- RG-316

Fairview Microwave 1130 Junction Dr. #100 Allen, TX 75013

Tel: 1-800-715-4396 / (972) 649-6678

Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com






dank> = Inches

Length

Typical Performance Data



Example: FMC0438315-12 = 12 inches long cable

FMC0438315-100cm = 100 cm long cable

RA SMA Male to BNC Female Bulkhead Cable RG-316 Coax from Fairview Microwave has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link to obtain additional part information: RA SMA Male to BNC Female Bulkhead Cable RG-316 Coax FMC0438315-XX


URL: http://www.fairviewmicrowave.com/ra-sma-male-bnc-female-cable-rg316-coax-fmc0438315-xx-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

1130 Junction Dr. #100 Allen, TX 75013 | Tel: 1-800-715-4396 / (972) 649-6678 / Fax: (972) 649-6689

Copyright © 2015





FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM	NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].					
RA SMA Male to BNC Female Bulkhead Cable RG-316 Coax	DWG NO FMCO438315-XX			CAGE CODE 3FKR5		
	CAD FILE 102114	SHEET	SCALE	N/A	SIZE A	5568