



3 Way Power Divider SMA Connectors From 2 GHz to 8 GHz Rated at 30 Watts

Electrical Specifications*

Description	Min	Тур	Max	Units	
Frequency Range	2		8	GHz	
Impedance		50		Ohms	
Insertion Loss		6.1		dB	
Input Power			30	Watts	
Input VSWR			1.4:1		
Output VSWR			1.4:1		
Isolation	18			dB	
Phase Balance		± 5		Degrees	
Flatness		0.8		dB	

^{*} Values at 25°C, sea level

Mechanical Specifications

 Temperature

 Operating Range
 -55 to +85 deg C

 Size
 2.63 in 66.8 mm

 Width
 1.5 in 38.1 mm

 Height
 0.4 in 10.16 mm

 Weight
 0.14065 lbs 63.8 g

Connectors

Description	Input Connector	Outer Connectors	
Туре	SMA Female	SMA Female	
Contact Material & Plating	Beryllium Copper, Gold	Beryllium Copper, Gold	
Body Material & Plating	Stainless Steel, Passivated	Stainless Steel, Passivated	

Compliance Certifications (visit www.FairviewMicrowave.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes

Values at 25 °C, sea level



Features:

- Input Connector: SMA Female
- Output Connectors: SMA Female
- Frequency Range: 2 to 8 GHz
- Design: Wilkinson
- Number of Output Ports: 3
- Housing Material and Plating:

Aluminum, Gray


Fairview Microwave 1130 Junction Dr. #100 Allen, TX 75013

Tel: 1-800-715-4396 / (972) 649-6678

Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com



Typical Performance Data



3 Way Power Divider SMA Connectors From 2 GHz to 8 GHz Rated at 30 Watts from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.


For additional information on this product, please click the following link: 3 Way Power Divider SMA Connectors From 2 GHz to 8 GHz Rated at 30 Watts MP0208-3

URL: http://www.fairviewmicrowave.com/3-way-power-divider-sma-8-ghz-30-watts-mp0208-3-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.







FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM	NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].				
3 Way Power Divider SMA Connectors From 2 GHz to 8 GHz Rated at 30 Watts	DWG NO MP0208-2		CAGE	CAGE CODE 3FKR5	
	CAD FILE 011415	SHEET	SCALE N/A	SIZE A	5568