

## 2.92mm Female (Jack) Bulkhead Connector For RG405 Cable, Solder



### SC5833

#### Configuration

- 2.92mm Female Connector
- 50 Ohms
- Straight Body Geometry
- Connector Interface Types: RG405
- Bulkhead

#### Features

- Operating Frequency of 40 GHz Max.
- Good VSWR of 1.3:1
- Gold Plated Beryllium Copper Contact
- Contact plating according to MIL-G-45204

#### Applications

- General Purpose Test
- Rack and Panel Mount Applications
- Custom Cable Assemblies

#### Description

2.92mm Female Bulkhead Standard Bulkhead Connector Solder Attachment for RG405 Cable, part number SC5833, from Fairview Microwave is in-stock and ships same day. This 2.92mm female connector operates up to a maximum frequency of 40 GHz and offers good VSWR of 1.3:1. Fairview's SC5833 bulkhead 2.92mm connector enables designers to make external connections on product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Fairview's 2.92mm female bulkhead connector SC5833 datasheet specifications and outline drawing are shown in this PDF below. Our extensive offering of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. From providing an I/O for a board design to creating a custom cable assembly configuration, Fairview Microwave has a connector solution to meet your needs. Fairview Microwave also has the expertise to build your custom cable assemblies for you and ship them same-day.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		40	GHz
VSWR			1.3:1	
Impedance		50		Ohms

#### Mechanical Specifications

##### Size

Length	0.64 in [16.26 mm]
Width	0.437 in [11.10 mm]
Height	0.437 in [11.10 mm]
Weight	0.011 lbs [4.99 g]
Mating Cycles	500 Cycles

2.92mm Female (Jack) Bulkhead Connector  
For RG405 Cable, Solder



SC5833

Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Gold MIL-G-45204
Insulation	PTFE	
Outer Conductor	Stainless Steel	Passivated
Body	Stainless Steel	Passivated

Environmental Specifications

Temperature	
Operating Range	-55 to +100 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data


Notes:

## 2.92mm Female (Jack) Bulkhead Connector For RG405 Cable, Solder




**SC5833**

### Assembly Instruction



1. PRE-TIN CABLE JACKET TO THE REFERENCE LENGTH AS SHOWN. ONLY FOR COPPER OUTER CONDUCTOR CABLE.



2. STRIP CABLE TO THE DIMENSIONS AS SHOWN TO EXPOSE CENTER CONDUCTOR AND DIELECTRIC. DO NOT NICK CENTER CONDUCTOR.
3. SLIDE CABLE INTO CONNECTOR INSURING CENTER CONDUCTOR MATES WITH CENTER PIN.
4. OUTER CONDUCTOR BOTTOMS OUT WITH BODY SHOULDER. SOLDER OUTER CONDUCTOR TO BODY.

## 2.92mm Female (Jack) Bulkhead Connector For RG405 Cable, Solder



### SC5833

2.92mm Female (Jack) Bulkhead Connector For RG405 Cable, Solder from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [2.92mm Female \(Jack\) Bulkhead Connector For RG405 Cable, Solder SC5833](https://www.fairviewmicrowave.com/2.92mm-female-rg405-connector-sc5833-p.aspx)

URL: <https://www.fairviewmicrowave.com/2.92mm-female-rg405-connector-sc5833-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

SC5833 CAD Drawing

2.92mm Female (Jack) Bulkhead Connector For RG405 Cable, Solder

