

SM2101 DATA SHEET

UHF Female (Jack) to UHF Female (Jack) Adapter, Nickel Plated Brass Body

UHF female to UHF female adapter part number SM2101 from Fairview Microwave is in-stock and ships same day. This Fairview UHF to UHF adapter has a female to female gender configuration. SM2101 UHF female to UHF female adapter operates to 300 MHz.

RF adapters can be used to enable connections between two connector types that would otherwise not mate. Certain RF adapter configurations can also be used to protect connectors on expensive equipment where the number of connect and disconnect cycles is high. An RF, microwave, or millimeter wave adapter is connected to the equipment and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Fairview Microwave also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

| Description | Min | Тур | Max | Units |
|-----------------|-----|-----|-----|-------|
| Frequency Range | DC | | 300 | MHz |
| DWV (AC) | | | 500 | Vrms |

Mechanical Specifications

Size

 Length
 1.11 in [28.07 mm]

 Width
 0.024 in [0.62 mm]

 Height
 0.024 in [0.62 mm]

 Weight
 0.04 lbs [18.82 q]

| Description | Connector 1 | Connector 2 |
|-------------|-------------|-------------|
| Туре | UHF Female | UHF Female |
| Polarity | Standard | Standard |

Material Specifications

| Description | Connector 1 | Connector 2 | |
|---------------------|---------------|---------------|--|
| Туре | UHF Female | UHF Female | |
| Contact Material | Brass | Brass | |
| Contact Plating | Silver | Silver | |
| Insulation Material | Thermoplastic | Thermoplastic | |
| Body Material | Brass | Brass | |
| Body Plating | Nickel | Nickel | |

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:



Configuration:

- UHF Female Connector 1
- UHF Female Connector 2
- •50 Ohm
- Straight Body Geometry

Features:

• Silver Plated Brass Contact

Applications:

• General Purpose Test


Fairview Microwave 301 Leora Ln., Suite 100 Lewisville, TX 75056 Tel: 1-800-715-4396 / (972) 649-6678 Fax: (972) 649-6689

www.fairviewmicrowave.com sales@fairviewmicrowave.com





Typical Performance Data



UHF Female (Jack) to UHF Female (Jack) Adapter, Nickel Plated Brass Body from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: UHF Female (Jack) to UHF Female (Jack) Adapter, Nickel Plated Brass Body SM2101

URL: https://www.fairviewmicrowave.com/uhf-female-uhf-female-adapter-sm2101-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.





