

2.4mm Male (Plug) to Mini SMP Male (Plug) Full Detent Adapter, Beryllium Copper Gold Body , 1.25 VSWR



SM8938

Configuration

- 2.4mm Male Connector 1
- Full Detent Mini SMP Male Connector 2
- 50 Ohms Impedance
- Straight Body Geometry

Features

- VSWR of 1.25:1 max up to 50 GHz
- Mini SMP interface meets MIL-STD-348
- Contact plating according to MIL-G-45204
- Gold Plated Beryllium Copper Contact

Applications

- Enables Between Series Connections
- General Purpose Test

Description

2.4mm male to Mini SMP male full detent adapter part number SM8938 from Fairview Microwave is in-stock and ships same day. This Fairview 2.4mm to Mini SMP adapter has a male to male gender configuration. SM8938 2.4mm male to Mini SMP male adapter operates to 50 GHz. The Fairview Microwave RF adapter provides excellent VSWR of 1.25:1 maximum. The 2.4mm connector mates mechanically with commercially available 1.85mm (V) connectors.

RF adapters can be used to enable connections between two connector types that would otherwise not mate. Certain RF adapter configurations can also be used to protect connectors on expensive equipment where the number of connect and disconnect cycles is high. An RF, microwave, or millimeter wave adapter is connected to the equipment and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Fairview Microwave also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		50	GHz
Impedance		50		Ohms
VSWR			1.25:1	

Electrical Specification Notes:
Values at 25°C, sea level.

Mechanical Specifications

Size

Length 0.89 in [22.61 mm]
Weight 0.01 lbs [3.86 g]

Description	Connector 1	Connector 2
Polarity	Standard	Standard
Interface Specification		MIL-STD-348

2.4mm Male (Plug) to Mini SMP Male (Plug) Full Detent Adapter, Beryllium Copper Gold Body , 1.25 VSWR



SM8938

Material Specifications

Description	Connector 1		Connector 2	
	Material	Plating	Material	Plating
Type	2.4mm Male		Full Detent Mini SMP Male	
Contact	Beryllium Copper	Gold MIL-G-45204	Beryllium Copper	Gold MIL-G-45204
Insulation	PTFE		PTFE	
Body	Beryllium Copper	Gold MIL-G-45204	Passivated Stainless Steel	AMS-QQ-P-35
Coupling Nut	Passivated Stainless Steel	AMS-QQ-P-35		

Environmental Specifications

Temperature

Operating Range -55 to 125 °C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

2.4mm Male (Plug) to Mini SMP Male (Plug) Full Detent Adapter, Beryllium Copper Gold Body , 1.25 VSWR from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [2.4mm Male \(Plug\) to Mini SMP Male \(Plug\) Full Detent Adapter, Beryllium Copper Gold Body , 1.25 VSWR SM8938](#)

URL: <https://www.fairviewmicrowave.com/2.4mm-male-mini-smp-male-full-detent-adapter-sm8938-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

SM8938 CAD Drawing

2.4mm Male (Plug) to Mini SMP Male (Plug) Full Detent Adapter, Beryllium Copper Gold Body , 1.25 VSWR

